





Datasheet ValkPro+ | ValkPro+ East-West

The concept

- Mounting system for PV-panels on flat roofs (commercial and domestic).
- · For south and east-west configurations.
- Fixed tilt angle of 10° (Landscape or Portrait) and 15° (Landscape).
- · Low ballast, shielded system with wind deflectors (south).

ValkPro+ vs. competitive systems

- Most cost effective solution.
- All metal connections, no plastic. This ensures high strength and reliability and makes the system easy to ground and for equalization of potential.
- Also suitable for roofs higher than 25 mtrs.
- Can be placed with ballast only on flat roofs with a maximum slope up to 5°.
 On roofs with a bigger slope, the system needs to be fixed to the roof.
- Universal integrated panel clamps (28-50 mm frame height).
- Suitable to be placed on roofs with gravel, "green roofs" or fixed on steel structures above the roof.
- Elevated mounting on roof for guaranteed drainage.

Additional features

- Designed and calculated according to latest building regulations.
- Low ballast and roof load, thanks to the use of wind deflectors and coupled rows.
- Easy and fast installation, thanks to limited number of parts and screw joints.
- Maximum logistical advantage, thanks to limited number of different parts and dimensions.
- · Smart solutions to hold cables and cable baskets.
- Easy to disassemble.

Panel formats

 ValkPro+ (south & east-west) is standard applicable for panels with the following dimensions:

| Configuration | Panel length min [mm] | Panel length max [mm]* | Panel width min [mm] | Panel width max [mm] | Pitch [mm] |
|----------------|--------------------------|---------------------------|-------------------------|-------------------------|------------|
| L10° South | 1520 | 2320 | 977 | 1200 | 1500 |
| L10° East-West | 1520 | 2320 | 977 | 1070 | 2300 |
| | | | 1071 | 1120 | 2400 |
| | | | 1121 | 1200 | 2500 |
| L15° South | 1520 | 2320 | 977 | 1200 | 1500 |
| L15° East-West | 1520 | 2320 | 977 | 1090 | 2300 |
| | | | 1091 | 1140 | 2400 |
| | | | 1141 | 1200 | 2500 |
| P10° South | 1559 | 2200 | 900 | 1500 | 2300 |
| P10° East-West | 1559 | 1680 | 900 | 1500 | 3500 |
| | 1681 | 1730 | 900 | 1500 | 3600 |
| | 1731 | 1830 | 900 | 1500 | 3800 |
| | 1831 | 2035 | 900 | 1500 | 4200 |
| | 2036 | 2135 | 900 | 1500 | 4400 |

^{*} Larger panel sizes are often also possible to mount on ValkPro+. Please contact Van der Valk Solar Systems for possibilities.